

Brisa Frontier — Ultrafabrics


Brisa Frontier is a relaxed grain available in a wide range of classic hues. Featuring our renowned breathable technology, this high-performing fabric provides ultimate seating comfort and softness. It's enhanced with water repellency, EPA-registered mildew defense, solar endurance, and colorfastness. Engineered for use inside or out, Brisa Frontier delivers both flexibility and functionality.




-
- Superior durability – industry-leading 16 weeks hydrolysis results
 - In pursuit of our goal to include at least 50% renewable and/or recycled resources across all collections, the backcloth of Brisa Frontier will transition to include recycled polyester and responsibly sourced rayon.
 - 200,000 double rubs (Wyzenbeek), 100,000 rubs (Martindale)
 - Breathable technology promotes airflow for ultimate seating comfort
 - Bleach cleanable (1:5 bleach/water solution)

An intelligent solution – the Ultrafabrics family of performance fabrics highlights boundary-pushing innovation where looks, feel, and performance matter.

Recommended for residential outdoor applications only. Suitable for all indoor applications/markets.



Outdoor Living



Breathable Comfort

Brisa Frontier from Ultrafabrics

Applications

Interior Upholstery, Exterior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
65% Polyester, 35% Rayon Backing

Weight:

Approx. 11.5 oz. Per Square Yard
Approx. 390 Grams Per Square Metre

Thickness:

Approx. 1.15 Millimetres

Width:

54 Inches / 137 Centimetres

Repeat:

8"V x 10.5"H / 203mm V x 267mm H

Performance

Abrasion:

ASTM D4157 / 200,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 100,000 Rubs (Martindale)*
*meets or exceeds

Hydrolysis:

16 Weeks
ASTM D3690 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating: ASTM D751

Tear Strength: ASTM D2261

Breaking Strength: ASTM D751

Tensile Strength: BS EN ISO 1421

Air Permeability: ASTM D737

Anti-mildew: ASTM G21

Sound Absorption: ASTM C423

Cold Crack: FTM 5874 / CFFA 6a

Blocking: ASTM D751, 89-93

Colorfastness

Light: ASTM G154, 1000 Hours
ISO 105 B02, Grade 8

Crocking: AATCC 8, Grade 4-5 Wet & Dry

Chlorinated Water: AATCC 162, Class 4-5

Perspiration: AATCC 15, Class 5

Sea (Salt) Water: AATCC 106, Class 4-5

Flammability Requirements

- ASTM E84 (Adhered) - Class A
- CA TB 117-2013 - Pass
- FMVSS 302 - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

- ASTM E84 (Unadhered)
- IMO FTPC Part 8
- BS EN 1021 Parts 1 & 2
- BS 5852 Source 0, 1 & 5 (Cig, Match & Crib 5)

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.

