



MARINE



HOSPITALITY



OFFICE



RESIDENTIAL



AVIATION



AUTOMOTIVE



RECREATION



DENTAL



HEALTHCARE

## A Touch of Natural Beauty for Active Lifestyles

Buffalino has the durability and strength to stand up to your active lifestyle. It meets or surpasses industry wear standards including bond strength, seam strength and tear strength. Buffalino exceeds 400,000 double rubs on the Wyzenbeek abrasion test method showing no wear and tear—that's 13X heavy-duty industry standards.

## You've Only Touched the Surface

Buffalino stays cool to the touch, even when exposed to sunlight. Soft and supple, Buffalino is tough enough to withstand kids and pets. Because it's inherently stain-resistant, no toxic aftercare is required to keep Buffalino looking its best.

## Earth Friendly

- Greenguard® Certified
- No PVC (Polyvinyl Chloride)
- No POPs (Persistent Organic Pollutants)
- No PBDEs (Polybrominated Diphenyl Ethers)
- No HFRs (Halogenated Flame Retardants)
- Meets the most stringent VOC standards
- No Plasticizers, Heavy Metals, Stabilizers or Phthalates
- No toxic by-products
- Over 99% of solvents recaptured and recycled
- ISO 9001 Certified Mill

## Maintenance & Care Instructions

Keep Ultrafabrics, LLC brand surfaces looking great by routine and proper maintenance. Clean regularly to prevent excessive dirt from accumulating. Follow these guidelines to extend the life of the fabric:

- Clean regularly with soap and water
- Wipe up spills as soon as they occur
- Remove stains with an alcohol-based cleaner like Fantastik®
- Disinfect using a 5:1 water/bleach solution
- Thoroughly rinse all cleaning solution residue with water
- Air dry

## SPECIFICATIONS

### ISO 9001-CERTIFIED PRODUCTION FACILITY

COMPOSITION: 100% POLYURETHANE SURFACE  
100% REINFORCED RAYON BACKING

WEIGHT: APPROX. 9.7 OZ. PER SQUARE YD  
(APPROX. 330 GRAMS PER SQUARE METRE)  
  
APPROX. 14.6 OZ. PER LINEAR YD  
(APPROX. 450 GRAMS PER LINEAR METRE)

THICKNESS: APPROX. 1.0 MM

WIDTH: 54 INCHES / 137 CENTIMETRES

PUT-UP: APPROX. 30 YDS / 27.5 METRES R.O.T.

### CHARACTERISTICS: MEETS OR EXCEEDS:

ABRASION: ASTM D 4157 / 400,000 DOUBLE RUBS  
BS 2543 / 100,000 RUBS (MARTINDALE)

TENSILE STRENGTH: ASTM D 1117

TEAR STRENGTH: ASTM D 1117

DIMENSIONAL CHANGE: ASTM D 3597

SEAM STRENGTH: ASTM D 751

STRETCH & SET: SAE J855

### COLORFASTNESS:

CROCKING: AATCC 8, CLASS 5 WET & DRY

LIGHT: AATCC 16E, AATCC 16A, CLASS 4-5

GAS: AATCC 23, CLASS 4-5

OZONE: AATCC 109, CLASS 5

### F/R RATING: (HFR FREE)

ASTM E 84 (ADHERED)	CLASS A
CA 117 E	CLASS 1
FMVSS 302 & 95/28 ANNEX IV	PASS
NFPA 260	CLASS 1
UFAC	CLASS 1

• CAN BE TREATED TO MEET FAR SPECIFICATIONS.  
• THIS FABRIC, WHEN TREATED AND/OR USED WITH OTHER COMPATIBLE FURNITURE COMPONENTS, HAS BEEN SHOWN TO PERFORM WELL UNDER THE FIRE TEST CONDITIONS OF CALIFORNIA TECHNICAL BULLETIN 133, BS 5852 PT 0, 1 & 5 (CRIB 5), IMO A.652(16), BS 7175 AND BS 5867 PART 2 TYPE B.

For more detailed information, visit us on the web at [www.ultrafabricsllc.com](http://www.ultrafabricsllc.com).



### ULTRA SURFACES. ULTRA RELEVANT.

Ultrafabrics, LLC | Hudson Point, 303 South Broadway | Tarrytown, NY 10591 | USA | T 914.460.1730 | F 914.347.1591 | [www.ultrafabricsllc.com](http://www.ultrafabricsllc.com)

Ultrafabrics Europe Ltd. | 19 The Warren, East Goscote | Leicestershire, LE7 3XA | United Kingdom | T +44.116.260.9625 | [ufe@ultrafabricsllc.com](mailto:ufe@ultrafabricsllc.com)

Made in Japan. UltraLeather™ and Brisa® are trademarks of Ultrafabrics, LLC.

