

Hammered

Ultra Innovation Collection



Durable, Beautiful, Contemporary Appeal

Hammered gives you the exceptional combination of stylish good looks and the strength to stand up to your active lifestyle. It meets or surpasses industry wear standards including bond strength, seam strength and tear strength. Hammered exceeds 400,000 double rubs on the Wyzenbeek abrasion test method showing no wear and tear – that’s 13X heavy-duty industry standards.

You’ve Only Touched the Surface

Hammered stays cool to the touch, even when exposed to sunlight. Soft and supple, Hammered is tough enough to withstand kids and pets. Because it’s inherently stain-resistant, no toxic aftercare is required to keep Hammered looking its best.

Earth Friendly

- Greenguard™ Certified
- No PVCs (Polyvinyl Chloride)
- No POPs (Persistent Organic Pollutants)
- No PBDEs (Polybrominated Diphenyl Ethers)
- No HFRs (Halogenated Flame Retardants)
- Meets the most stringent VOC standards
- No Plasticizers, Heavy Metals, Stabilizers or Phthalates
- No toxic by-products
- Over 99% of solvents recaptured and recycled
- ISO 9001 Certified Mill

Maintenance & Care Instructions

Keep Ultrafabrics, LLC brand surfaces looking great by routine and proper maintenance. Clean regularly to prevent excessive dirt from accumulating. Follow these guidelines to extend the life of the fabric:

- Clean regularly with soap and water
- Wipe up spills as soon as they occur
- Remove stains with an alcohol-based cleaner like Fantastik®
- Disinfect using a 5:1 water/bleach solution
- Thoroughly rinse all cleaning solution residue with water
- Air dry

SPECIFICATIONS

ISO 9001-CERTIFIED PRODUCTION FACILITY

COMPOSITION:	100% POLYURETHANE SURFACE 100% REINFORCED RAYON BACKING
WEIGHT:	APPROX. 9.7 OZ. PER SQUARE YD (APPROX. 330 GRAMS PER SQUARE METRE) APPROX. 14.6 OZ. PER LINEAR YD (APPROX. 450 GRAMS PER LINEAR METRE)
THICKNESS:	APPROX. 1.0 MM
WIDTH:	54 INCHES / 137 CENTIMETRES
PUT-UP:	APPROX. 30 YDS / 27.5 METRES R.O.T.

CHARACTERISTICS: MEETS OR EXCEEDS:

ABRASION:	ASTM D 4157 / 400,000 DOUBLE RUBS BS 2543 / 180,000 RUBS (MARTINDALE)
TENSILE STRENGTH:	ASTM D 1117
TEAR STRENGTH:	ASTM D 1117
DIMENSIONAL CHANGE:	ASTM D 3597
SEAM STRENGTH:	ASTM D 751
STRETCH & SET:	SAE J855

COLORFASTNESS:

CROCKING:	AATCC 8, CLASS 5 WET & DRY
LIGHT:	AATCC 16E, AATCC 16A, CLASS 4-5
GAS:	AATCC 23, CLASS 4-5
OZONE:	AATCC 109, CLASS 5

F/R RATING: (HFR FREE)

	ASTM E 84 (ADHERED) CA 117 E FMVSS 302 NFPA 260 UFAC	CLASS A CLASS 1 PASS CLASS 1 CLASS 1
--	--	--

• CAN BE TREATED TO MEET FAR SPECIFICATIONS.
• THIS FABRIC, WHEN TREATED AND/OR USED WITH OTHER COMPATIBLE FURNITURE COMPONENTS, HAS BEEN SHOWN TO PERFORM WELL UNDER THE FIRE TEST CONDITIONS OF CALIFORNIA TECHNICAL BULLETIN 133 AND BS 5852 SOURCE 5 ("CRIB 5"), IMO A.652(16), BS 7175 AND BS 5867 PART 2 TYPE B.

For more detailed information, visit us on the web at www.ultrafabricsllc.com or call 914.460.1730.



ULTRA SURFACES. ULTRA RELEVANT.

Ultrafabrics, LLC | Hudson Point, 303 South Broadway | Tarrytown, NY 10591 | USA | T 914.460.1730 | F 914.347.1591 | www.ultrafabricsllc.com
Ultrafabrics Europe Ltd. | 19 The Warren, East Goscote | Leicestershire, LE7 3XA | United Kingdom | T +44.116.260.9625 | ufe@ultrafabricsllc.com
Made in Japan. Ultraleather™ and Brisa® are trademarks of Ultrafabrics, LLC.

