

Pony Outdoor

Ultra Lifestyle Collection



Breathability, Solar Endurance, Mildew Resistance

Pony Outdoor is engineered to stand up to high wear and extended exposure to sunlight. It exceeds industry standards of 1,000 hours for QUV testing. It meets or surpasses industry wear standards including bond strength, seam strength and tear strength. Pony Outdoor exceeds 200,000 double rubs on the Wyzenbeek abrasion test method showing no wear and tear – that's 6x heavy-duty industry standards. Add mildew resistance technology, and you've got the ideal surface for your life outdoors.

Cool – Even When it's Hot

Pony Outdoor stays cool to the touch, even when exposed to sunlight. It cools down faster than leather and vinyl (PVC) – a benefit that makes your life easier and more comfortable than ever, especially on hot summer days. Because it's inherently stain-resistant, no toxic aftercare is required to keep Pony Outdoor looking its best.

Earth Friendly

- Greenguard® Certified
- No PVC (Polyvinyl Chloride)
- No POPs (Persistent Organic Pollutants)
- No PBDEs (Polybrominated Diphenyl Ethers)
- No HFRS (Halogenated Flame Retardants)
- Meets the most stringent VOC standards
- No Plasticizers, Heavy Metals, Stabilizers or Phthalates
- No toxic by-products
- Over 99% of solvents recaptured and recycled
- ISO 9001 Certified Mill

Maintenance & Care Instructions

Keep Ultrafabrics, LLC brand surfaces looking great by routine and proper maintenance. Clean regularly to prevent excessive dirt from accumulating. Follow these guidelines to extend the life of the fabric:

- Clean regularly with soap and water
- Wipe up spills as soon as they occur
- Remove stains with an alcohol-based cleaner like Fantastik®
- Disinfect using a 5:1 water/bleach solution
- Thoroughly rinse all cleaning solution residue with water
- Air dry

For more detailed information, please call 914.460.1730 or visit us on the web at www.ultrafabricsllc.com.

SPECIFICATIONS

ISO 9001-CERTIFIED PRODUCTION FACILITY

COMPOSITION:	100% POLYURETHANE SURFACE 65% POLYESTER, 35% RAYON BACKING
WEIGHT:	APPROX. 11.2 OZ. PER SQUARE YD (APPROX. 380 GRAMS PER SQUARE METRE) APPROX. 16.8 OZ. PER LINEAR YD (APPROX. 520 GRAMS PER LINEAR METRE)
THICKNESS:	APPROX. 1.2 MM
WIDTH:	54 INCHES / 137 CENTIMETRES
PUT-UP:	APPROX. 30 YDS / 27.5 METRES R.O.T.

CHARACTERISTICS: MEETS OR EXCEEDS:

ABRASION:	ASTM D 4157 / 200,000 DOUBLE RUBS BS 2543 / 100,000 RUBS (MARTINDALE)
TENSILE STRENGTH:	ASTM D 1117
TEAR STRENGTH:	ASTM D 1117
DIMENSIONAL CHANGE:	ASTM D 3597
SEAM STRENGTH:	ASTM D 751
STRETCH & SET:	SAE J855
ANTI - MILDEW:	ASTM G 21
AIR PERMEABILITY:	ASTM D 737
UV:	ASTM G 154 – 1,000 HOURS

COLORFASTNESS:

CROCKING:	AATCC 8, CLASS 5 WET & DRY
GAS:	AATCC 23, CLASS 5
OZONE:	AATCC 109, CLASS 5
SEA (SALT) WATER:	AATCC 106, CLASS 5
CHLORINATED WATER:	AATCC 162, CLASS 5
PERSPIRATION:	AATCC 15, CLASS 5

F/R RATING: (HFR FREE)

CA 117 E	CLASS 1
FMVSS 302	PASS
NFPA 260	CLASS 1
UFAC	CLASS 1

- CAN BE TREATED TO MEET FAR SPECIFICATIONS.
- THIS FABRIC, WHEN TREATED AND/OR USED WITH OTHER COMPATIBLE FURNITURE COMPONENTS, HAS BEEN SHOWN TO PERFORM WELL UNDER THE FIRE TEST CONDITIONS OF CALIFORNIA TECHNICAL BULLETIN 133 AND BS 5852 SOURCE 5 ("CRIB 5"), IMO A.652(16), BS 7175 AND BS 5867 PART 2 TYPE B.

Remember:

- All outdoor products should be stored in a dry, well ventilated area
- Ultrafabrics mildew resistant surfaces do not promote mildew growth, however, mildew may grow on dirt and other foreign substances that are not removed from the fabric
- The frequency of cleaning will vary greatly depending upon the local outdoor environment in which the product is used
- Cushions should not remain wet or be covered, as this will increase the chances of mildew growth occurring



ULTRA SURFACES. ULTRA RELEVANT.

Ultrafabrics, LLC | Hudson Point, 303 South Broadway | Tarrytown, NY 10591 | USA | T 914.460.1730 | F 914.347.1591 | www.ultrafabricsllc.com
Ultrafabrics Europe Ltd. | 19 The Warren, East Goscote | Leicestershire, LE7 3XA | United Kingdom | T +44.116.260.9625 | ufe@ultrafabricsllc.com

Made in Japan. Ultraleather™ and Brisa® are trademarks of Ultrafabrics, LLC.

