

Ultraleather™ Plus

Ultraleather Collection



Extreme Durability and Antimicrobial Protection

Ultraleather™ Plus combines extreme durability with a naturally bonded antimicrobial component that is laboratory proven to reduce microbial growth by over 99%, making it ideal for healthcare and other high wear applications. It meets or surpasses industry wear standards including bond strength, seam strength and tear strength. Ultraleather Plus exceeds 500,000 double rubs on the Wyzenbeek abrasion test method showing no wear and tear – that’s 16X heavy-duty industry standards.

You’ve Only Touched the Surface

Ultraleather Plus stays cool to the touch, even when exposed to sunlight. Soft and supple, Ultraleather Plus is tough enough to withstand kids and pets. Because it’s inherently stain-resistant, no toxic aftercare is required to keep Ultraleather Plus looking its best.

Earth Friendly

- Greenguard™ Certified
- No PVC (Polyvinyl Chloride)
- No POPs (Persistent Organic Pollutants)
- No PBDEs (Polybrominated Diphenyl Ethers)
- No HFRs (Halogenated Flame Retardants)
- Meets the most stringent VOC standards
- No Plasticizers, Heavy Metals, Stabilizers or Phthalates
- No toxic by-products
- Over 99% of solvents recaptured and recycled
- ISO 9001 Certified Mill

Maintenance & Care Instructions

Keep Ultrafabrics, LLC brand surfaces looking great by routine and proper maintenance. Clean regularly to prevent excessive dirt from accumulating. Follow these guidelines to extend the life of the fabric:

- Clean regularly with soap and water
- Wipe up spills as soon as they occur
- Remove stains with an alcohol-based cleaner like Fantastik®
- Disinfect using a 5:1 water/bleach solution
- Thoroughly rinse all cleaning solution residue with water
- Air dry

SPECIFICATIONS

ISO 9001-CERTIFIED PRODUCTION FACILITY

COMPOSITION:	100% POLYURETHANE SURFACE 65% POLYESTER, 35% RAYON BACKING	
WEIGHT:	APPROX. 12.4 OZ. PER SQUARE YD (APPROX. 420 GRAMS PER SQUARE METRE)	
	APPROX. 18.6 OZ. PER LINEAR YD (APPROX. 575 GRAMS PER LINEAR METRE)	
THICKNESS:	APPROX. 1.1 MM	
WIDTH:	54 INCHES / 137 CENTIMETRES	
PUT-UP:	APPROX. 30 YDS / 27.5 METRES R.O.T.	

CHARACTERISTICS:	MEETS OR EXCEEDS:	
ABRASION:	ASTM D 4157 / 500,000 DOUBLE RUBS BS 2543 / 100,000 RUBS (MARTINDALE)	
TENSILE STRENGTH:	ASTM D 1117	
TEAR STRENGTH:	ASTM D 1117	
DIMENSIONAL CHANGE:	ASTM D 3597	
SEAM STRENGTH:	ASTM D 751	
STRETCH & SET:	SAE J855	
ANTIMICROBIAL	ASTM E 2180	

COLORFASTNESS:		
CROCKING:	AATCC 8, CLASS 5 WET & DRY	
LIGHT	AATCC 16-3, CLASS 5	
GAS:	AATCC 23, CLASS 5	
OZONE:	AATCC 109, CLASS 5	

F/R RATING: (HFR FREE)		
	ASTM E 84 (ADHERED) CA 117 E FMVSS 302 & 95/28 ANNEX IV NFPA 260 UFAC	CLASS A CLASS 1 PASS CLASS 1 CLASS 1

• CAN BE TREATED TO MEET FAR SPECIFICATIONS.
 • THIS FABRIC, WHEN TREATED AND/OR USED WITH OTHER COMPATIBLE FURNITURE COMPONENTS, HAS BEEN SHOWN TO PERFORM WELL UNDER THE FIRE TEST CONDITIONS OF CALIFORNIA TECHNICAL BULLETIN 133, BS 5852 PT 0, 1 & 5 (CRIB 5), IMO A.652(16), BS 7175 AND BS 5867 PART 2 TYPE B.

For more detailed information, visit us on the web at www.ultrafabricsllc.com or call 914.460.1730.



ULTRA SURFACES. ULTRA RELEVANT.

Ultrafabrics, LLC | Hudson Point, 303 South Broadway | Tarrytown, NY 10591 | USA | T 914.460.1730 | F 914.347.1591 | www.ultrafabricsllc.com
 Ultrafabrics Europe Ltd. | 19 The Warren, East Goscote | Leicestershire, LE7 3XA | United Kingdom | T +44.116.260.9625 | ufe@ultrafabricsllc.com
 Made in Japan. Ultraleather™ and Brisa® are trademarks of Ultrafabrics, LLC.

